

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number  
WO 2005/041009 A2

(51) International Patent Classification<sup>7</sup>: G06F 3/00

(21) International Application Number:  
PCT/GB2004/004025

(22) International Filing Date:  
22 September 2004 (22.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0322875.6 30 September 2003 (30.09.2003) GB

(71) Applicant (for all designated States except US): **BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY** [GB/GB]; 81 Newgate Street, London, Greater London EC1A 7AJ (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HARDWICK, Andrew, John** [GB/GB]; 55 Reading Road, Ipswich Suffolk IP4 4NR (GB).

(74) Agent: **BRADLEY, David, William**; BT Group Legal Intellectual Property Department, PPC5A, BT Centre, 81 Newgate Street, London, Greater London EC1A 7AJ (GB).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HAPTICS TRANSMISSION SYSTEMS

### Hardware



(57) Abstract: In order to overcome the problems arising from network latency in haptic transmission systems a local PC (23, 24) attempts to build a force/position model of a remote haptic device (22, 21) so that when packetised position data is received through the network 5 signals controlling the motors of the local haptic device (21, 22) may be adjusted to reflect a predicted position still to be received. By using a local data model of the remote environment, the prediction may take account of reaction forces from objects/textures being simulated locally.

Best Available Copy

WO 2005/041009 A2



**Published:**

— without international search report and to be republished upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Best Available Copy**